



# Agilent 33250A Function/Arbitrary Waveform Generator

Data Sheet



- 80 MHz sine and square wave outputs
- Sine, square, ramp, noise and other waveforms
- 50 MHz pulse waveforms with variable rise/fall times
- 12-bit, 200 MSa/s, 64K-point deep arbitrary waveform

## Built-in Versatility

AM, FM and FSK capabilities make it easy to modulate waveforms with or without a separate source. Linear or logarithmic sweeps can be performed with a programmable frequency marker signal. Programmable burst count and gating allow you to further customize your signal.

For system applications, both GPIB and RS-232 interfaces are standard, and support full programmability using SCPI commands.

## Color Graphical Display

The unique design of the 33250A combines a low-profile instrument with the benefits of a color graphical display. Now you can display multiple waveform parameters at the same time. The graphical interface also allows you to modify arbitrary waveforms quickly and easily.

## Timebase Stability and Clock Reference

The 33250A TCXO timebase gives you frequency accuracy of 2 ppm for your most demanding applications. The external clock reference input/output lets you synchronize to an external 10 MHz clock, to another 33250A, or to another Agilent 332XXA Function/Arbitrary Waveform Generator. Phase adjustments can be made from the front panel or via a computer interface, allowing precise phase calibration and adjustment.

## Standard Waveforms

The Agilent Technologies 33250A Function/Arbitrary Waveform Generator uses direct digital-synthesis techniques to create a stable, accurate output on all waveforms, down to 1  $\mu$ Hz frequency resolution. The benefits are apparent in every signal you produce, from the sine wave frequency accuracy to the fast rise/fall times of square waves, to the ramp linearity.

Front-panel operation of the 33250A is straightforward and user friendly. The knob or numeric keypad can be used to adjust frequency, amplitude and offset. You can even enter voltage values directly in Vpp, Vrms, dBm, or high/low levels. Timing parameters can be entered in hertz (Hz) or seconds.

## Custom Waveform Generation

Why settle for a basic function generator when you can get arbitrary waveforms at no extra cost? With the 33250A, you can generate arbitrary waveforms with 12-bit vertical resolution, 64K memory depth, and a sample rate of 200 MSa/s. You can also store up to four 64K-deep arbitrary waveforms in non-volatile memory with user-defined names to help you find the right waveform when you need it most.

The included Agilent IntuiLink software allows you to easily create, edit, and download complex waveforms using the IntuiLink Arbitrary Waveform Editor. Or you can capture a waveform using IntuiLink oscilloscope or DMM and send it to the 33250A for output. For programmers, ActiveX components can be used to control the instrument using SCPI commands. IntuiLink provides the tools to easily create, download, and manage waveforms for your 33250A. To find out more about IntuiLink, visit [www.agilent.com/find/intuilink](http://www.agilent.com/find/intuilink).

## Pulse Generation

The 33250A can generate simple pulses up to 50 MHz. With variable edge time, pulse width and voltage level, the 33250A is ideally suited to a wide variety of pulse applications.



Agilent Technologies

## Waveforms

<b>Standard</b>	sine, square, pulse, ramp, noise, sin(x)/x, exponential rise, exponential fall, cardiac, DC volts
<b>Arbitrary</b>	
Waveform length	1 to 64K points
Amplitude resolution	12 bits (including sign)
Repetition rate	1 $\mu$ Hz to 25 MHz
Sample rate	200 MSa/s
Filter bandwidth	50 MHz
Non-vol. memory	Four (4) 64K waveforms

## Frequency Characteristics

Sine	1 $\mu$ Hz to 80 MHz
Square	1 $\mu$ Hz to 80 MHz
Pulse	500 $\mu$ Hz to 50 MHz
Arb	1 $\mu$ Hz to 25 MHz
Ramp	1 $\mu$ Hz to 1 MHz
White noise	50 MHz bandwidth
Resolution	1 $\mu$ Hz; except pulse, 5 digits
Accuracy (1 year)	2 ppm, 18°C to 28°C 3 ppm, 0°C to 55°C

## Sinewave Spectral Purity

<b>Harmonic distortion</b>	$\leq 3 \text{ Vpp}^1$	$> 3 \text{ Vpp}$
DC to 1 MHz	-60 dBc	-55 dBc
1 MHz to 5 MHz	-57 dBc	-45 dBc
5 MHz to 80 MHz	-37 dBc <sup>2</sup>	-30 dBc <sup>2</sup>

## Total harmonic distortion

DC to 20 kHz	< 0.2% + 0.1 mVrms
Spurious (non-harmonic) <sup>3</sup>	
DC to 1 MHz	-60 dBc
1 MHz to 20 MHz	-50 dBc
20 MHz 80 MHz	-50 dBc + 6 dBc/octave

## Phase noise (30 kHz band)

10 MHz	<-65 dBc (typical)
80 MHz	<-47 dBc (typical)

## Signal Characteristics

<b>Squarewave</b>	
Rise/Fall time	< 8 ns <sup>4</sup>
Overshoot	< 5%
Asymmetry	1% of period + 1 ns
Jitter (rms)	
< 2 MHz	0.01% + 525 ps
$\geq 2$ MHz	0.1% + 75 ps
Duty cycle	
$\leq 25$ MHz	20.0% to 80.0%
25 MHz to 50 MHz	40.0% to 60.0%
50 MHz to 80 MHz	50.0% (fixed)

## Pulse

Period	20.00 ns to 2000.0 s
Pulse width	8.0 ns to 1999.9 s
Variable edge time	5.00 ns to 1.00 ms
Overshoot	< 5%
Jitter (rms)	100 ppm + 50 ps

## Ramp

Linearity	< 0.1% of peak output
Symmetry	0.0% to 100.0%

## Arb

Minimum edge time	< 10 ns
Linearity	< 0.1% of peak output
Settling time	< 50 ns to 0.5% of final value
Jitter (rms)	30 ppm + 2.5 ns

## Output Characteristics

<b>Amplitude</b> (into 50 $\Omega$ )	10 mVpp to 10 Vpp <sup>5</sup>
Accuracy (at 1 kHz, >10 mVpp, Autorange on)	$\pm 1\%$ of setting $\pm 1$ mVpp
Flatness (sinewave relative to 1 kHz, Autorange on)	
< 10 MHz	$\pm 1\%$ (0.1 dB) <sup>6</sup>
10 MHz to 50 MHz	$\pm 2\%$ (0.2 dB)
50 MHz to 80 MHz	$\pm 5\%$ (0.4 dB)
Units	Vpp, Vrms, dBm, high and low level
Resolution	0.1 mV or 4 digits

<b>Offset</b> (into 50 $\Omega$ )	$\pm 5$ Vpk ac + dc
Accuracy	1% of setting + 2 mV + 0.5% of amplitude

## Waveform Output

Impedance	50 $\Omega$ typical (fixed) >10 M $\Omega$ (output disabled)
Isolation	42 Vpk maximum to earth
Protection	short-circuit protected <sup>7</sup> ; overload relay automatically disables main output

## Modulation Characteristics

<b>AM</b>	
Carrier waveforms	sine, square, ramp, and arb
Mod. waveforms	sine, square, ramp, noise, and arb
Mod. frequency	2 MHz to 20 kHz
Depth	0.0% to 120.0%
Source	internal/external

<b>FM</b>	
Carrier waveforms	sine, square, ramp, and arb
Mod. waveforms	sine, square, ramp, noise, and arb
Mod. frequency	2 MHz to 20 kHz
Peak deviation	DC to 80 MHz
Source	internal/external

<b>FSK</b>	
Carrier waveforms	sine, square, ramp, and arb
Mod. waveform	50% duty cycle square
Internal rate	2 MHz to 100 kHz
Frequency range	1 $\mu$ Hz to 80 MHz
Source	internal/external

## External Modulation Input

Voltage range	$\pm 5$ V full scale
Input impedance	10 $\Omega$
Frequency	DC to 20 kHz
Latency	< 70 $\mu$ s typical

## Burst

Waveforms	sine, square, ramp, pulse, arb, and noise
Frequency	1 $\mu$ Hz to 80 MHz <sup>8</sup>
Burst count	1 to 1,000,000 cycles or infinite
Start/Stop phase	-360.0° to +360.0°
Internal period	1 ms to 500 s
Gate source	external trigger
Trigger source	single manual trigger, internal, external trig
Trigger delay	
N-cycle, infinite	0.0 ns to 85.000 sec

## Sweep

Waveforms	sine, square, ramp, and arb
Type	linear and logarithmic
Direction	up or down
Start F/Stop F	100 $\mu$ Hz to 80 MHz
Sweep time	1 ms to 500 s
Trigger	single manual trigger, internal, external trig falling edge of sync signal (programmable)
Marker	

## System Characteristics

### Configuration Times (typical)<sup>9</sup>

Function change	
Standard	100 ms
Pulse	660 ms
Built-in arb	220 ms
Frequency change	20 ms
Amplitude change	50 ms
Offset change	50 ms
Select user arb	< 900 ms for < 16K pts.
Modulation change	< 200 ms

### Arb Download Times GPIB/RS-232 (115Kbps)

Arb Length	Binary	ASCII Integer	ASCII Real
64K points	48 sec	112 sec	186 sec
16K points	12 sec	28 sec	44 sec
8K points	6 sec	14 sec	22 sec
4K points	3 sec	7 sec	11 sec
2K points	1.5 sec	3.5 sec	5.5 sec

## Trigger Characteristics

### Trigger input

Input level	TTL compatible
Slope	rising or falling, (selectable)
Pulse width	> 100 ns
Input impedance	10 k $\Omega$ , DC coupled
Latency	
Burst	< 100 ns (typical)
Sweep	< 10 $\mu$ s (typical)
Jitter (rms)	
Burst	1 ns; except pulse, 300 ps
Sweep	2.5 $\mu$ s

### Trigger output

Level	TTL compatible into 50 $\Omega$
Pulse width	> 450 ns
Maximum rate	1 MHz
Fanout	$\leq$ 4 Agilent 33250A's (or equivalent)

## Clock Reference

### Phase Offset

Range	-360° to +360°
Resolution	0.001°

### External Reference Input

Lock range	10 MHz $\pm$ 35 kHz
Level	100 mVpp to 5 Vpp
Impedance	1 k $\Omega$ nominal, ac coupled
Lock time	< 2 s

### Internal Reference Output

Frequency	10 MHz
Level	632 mVpp (0 dbm), nominal
Impedance	50 $\Omega$ nominal, ac coupled

## Sync Output

Level	TTL compatible into > 1 k $\Omega$
Impedance	50 $\Omega$ nominal

## General

Power supply	100-240 V, 50-60 Hz 100-127 V, 50-400 Hz
Power consumption	140 VA
Operating temp.	0°C to 55°C
Storage temp.	-30°C to 70°C
Stored states	4 named user configurations default or last
Power on state	default or last
Interface	IEEE-488 and RS-232 std.
Language	SCPI-1997, IEEE-488.2
Dimensions (WxHxD)	
Bench top	254 x 104 x 374 mm
Rackmount	213 x 89 x 348 mm
Weight	4.6 kg
Safety designed to	EN61010-1, CSA1010.1, UL-311-1
EMC tested to	IEC-61326-1 IEC-61000-4-3 criteria B IEC-61000-4-6 criteria B
Vibration and shock	MIL-T-28800E, Type III, Class 5
Acoustic noise	40 dBA
Warm-up time	1 hour
Calibration interval	1 year
Warranty	1 year

<sup>1</sup> Harmonic distortion at low amplitudes is limited by a -70 dBm floor

<sup>2</sup> Harmonic distortion at 40 MHz only is -33 dBc

<sup>3</sup> Spurious noise at low amplitudes is limited by a -75 dBm floor

<sup>4</sup> Edge time decreased at higher frequency, 3.5 nS (typical)

<sup>5</sup> 20 mVpp to 20 Vpp into open-circuit load

<sup>6</sup> dB rounded to 1 digit, instrument adheres to “%” specification

<sup>7</sup> Short-circuit protected to ground at all times

<sup>8</sup> Sine and square waveforms above 25 MHz only with infinite burst count

<sup>9</sup> Time to change parameter and output new signal

### Ordering Information

#### Agilent 33250A

80 MHz Function/Arbitrary Waveform Generator

#### Accessories included

Operating manual, service manual, quick reference guide, IntuiLink waveform editor software, test data, RS-232 cable, and power cord (see language option).

#### Options

**Opt. 0B0** Delete manual

**Opt. 1CM** Rackmount kit (also sold as Agilent 34190A)

**Opt. A6J** ANSI Z540 calibration

**Opt. AB0** Taiwan: Chinese manual

**Opt. AB1** Korea: Korean manual

**Opt. AB2** China: Chinese manual

**Opt. ABA** English: English manual

**Opt. ABD** Germany: German manual

**Opt. ABF** France: French manual

**Opt. ABJ** Japan: Japanese manual

#### Other Accessories

**34131A** Carrying case

**34161A** Accessory pouch

**34190A** Rackmount kit\*

\*For racking two 33250As side-by-side, order the following items: Lock-link kit (p/n 5061-9694), Flange kit (p/n 5063-9212)



#### Agilent Email Updates

[www.agilent.com/find/emailupdates](http://www.agilent.com/find/emailupdates)

Get the latest information on the products and applications you select.



#### Agilent Direct

[www.agilent.com/find/agilentdirect](http://www.agilent.com/find/agilentdirect)

Quickly choose and use your test equipment solutions with confidence.

### Remove all doubt

Our repair and calibration services will get your equipment back to you, performing like new, when promised. You will get full value out of your Agilent equipment throughout its lifetime. Your equipment will be serviced by Agilent-trained technicians using the latest factory calibration procedures, automated repair diagnostics and genuine parts. You will always have the utmost confidence in your measurements.

Agilent offers a wide range of additional expert test and measurement services for your equipment, including initial start-up assistance onsite education and training, as well as design, system integration, and project management.

For more information on repair and calibration services, go to:

[www.agilent.com/find/removealldoubt](http://www.agilent.com/find/removealldoubt)

For more information on Agilent Technologies' products, applications or services, please contact your local Agilent office. The complete list is available at:

[www.agilent.com/find/contactus](http://www.agilent.com/find/contactus)

#### Americas

Canada	(877) 894-4414
Latin America	305 269 7500
United States	(800) 829-4444

#### Asia Pacific

Australia	1 800 629 485
China	800 810 0189
Hong Kong	800 938 693
India	1 800 112 929
Japan	0120 (421) 345
Korea	080 769 0800
Malaysia	1 800 888 848
Singapore	1 800 375 8100
Taiwan	0800 047 866
Thailand	1 800 226 008

#### Europe & Middle East

Austria	01 36027 71571
Belgium	32 (0) 2 404 93 40
Denmark	45 70 13 15 15
Finland	358 (0) 10 855 2100
France	0825 010 700*
Germany	07031 464 6333
Ireland	1890 924 204
Israel	972-3-9288-504/544
Italy	39 02 92 60 8484
Netherlands	31 (0) 20 547 2111
Spain	34 (91) 631 3300
Sweden	0200-88 22 55
Switzerland	0800 80 53 53
United Kingdom	44 (0) 118 9276201

Other European Countries:

[www.agilent.com/find/contactus](http://www.agilent.com/find/contactus)

Revised: March 24, 2009

Product specifications and descriptions in this document subject to change without notice.

© Agilent Technologies, Inc. 2009  
Printed in USA May 5, 2009  
5968-8807EN

